



A R K T U R A


Vapor[®] Trail



Ceiling & Wall **Panels**


Our Key Features

Vapor® Trail powder-coated aluminum torsion spring panels feature a linear design of multi-sized circles, creating a flowing effect designed to evoke emotion. Each line of larger circles tapers off with smaller circles to create a trail you'll want to follow, especially when paired with our integrated lighting backer. But if you don't want to hear people following the trail, add our Soft Sound backer and reduce excess noise.



Reduce Noise & Enhance Acoustics

Vapor®'s optional Soft Sound® backer material reduces the impact of noise from everyday annoyances like ringing, typing, and chatter resulting in a more pleasant and productive environment. The Soft Sound® backer works in concert with the design to help reduce and control reverberations leaving a lasting impression at scales ranging from assembly halls to conference rooms.




Easy Installation & Access

Vapor® panels offer easy install, using quick torsion spring attachment across standard ceiling grid systems or simple wall attachment using our Vertika® channel system.




Superior Flatness & Strength

Vapor® panels are manufactured from aluminum that is on average 50% thicker than the competition, which in combination with our precision processes result in unrivaled flatness.




Preconfigured Solutions

Vapor® panels are scalable, seamlessly tileable preconfigured solutions designed with a dynamic array of criteria and effects in mind. Choose from our growing library of patterns to uniquely impact your project.



Integrated Lighting Options

Arktura's Vapor® line makes it easy to seamlessly add illumination and lighting effects to your projects, through available integrated InLine and Backlighting options.




Continuous Pattern Aesthetic

Achieve uninterrupted patterning across your space. Vapor® patterns have perforations that wrap around the edges of each panel, concealing where patterns start and end.

Inspiration



Create Dynamic Wall to Ceiling Transitions



Illuminate your Space with Arktura Backlighting



Make an Eye-Catching Entrance


Overview

- 1 Understanding the System
- 2 Optional Accessories
- 3 Available Finishes
- 4 Product Specifications

1 Understanding the System


Standard Panel

Vapor® is a modular accessible aluminum panel system designed to work with torsion grid. Customization is available.



Seamlessly Join Walls & Ceilings

Vapor® easily transitions from one plane to another and around corners.



1 Understanding the System

Understanding the Panel

The pattern surface is created using 4 unique tiles in a specific arrangement that minimizes visual repetition across your space.

Panel A: 24% Open


Panel B: 22% Open

Panel C: 23% Open

Panel D: 26% Open

* Vertika® Trim


Wall Section



Ceiling Section



Panel Configuration, Wall or Ceiling



All dimensions are in mm unless otherwise specified.

All dimensions nominal.

1

Understanding the System

Accessory Options - Ceiling



- Frosted light diffusing backer
- 12mm acoustic backer
- Backlight
- InLine downlight

 Check out our Configuration examples on PAGE 10.

* A Specific InLine light panel is used to accommodate the width of the fixture within the 600mm width.


Torsion Spring Adapter Clip

Interested in using standard t-grid?
Use our optional Torsion Spring Adapter Clip.



Attachment System - Ceiling

Torsion Spring clips allow for rapid install and easy access for maintenance above the grid post install.




1 Understanding the System

Accessory Options - Wall

- Frosted light diffusing backer
- 12mm acoustic backer
- Backlight
- InLine light


i Check out our Configuration examples on PAGE 10.

* A Specific Inline light panel is used to accommodate the width of the fixture within the 600mm width.



Attachment System - Wall


Panels are easily installed or removed by sliding onto or lifting off from the system's Vertika® channel hooks.



2

Optional Accessories

Lighting


**Backlighting**

Arkтура Backlighting allows you to fully illuminate your ceiling and wall panel installs, creating beautiful evenly lit surfaces. These fixtures are available in high and low output versions, both dimmable. See Backlighting specs details on PAGE 14.


**InLine Lighting**

Our InLine Light sits flush with the face of the panels while conveniently attaching to the bottom of the grid. Fixtures: 1200 and 2400 lengths. A special side-light Vapor® panel allows the light to straddle its 1200mm edge while staying within a 600mm overall width. See Inline Lighting specs details on PAGE 15.

Backers

**Acoustic Backer**

We offer various options of Soft Sound® panel inserts to achieve a variety of NRC ratings. Please refer to our True NRC® table of ratings.

**Translucent Backer**

Our proprietary light diffusing backers can be used to create a functional or decorative lighting effect in any space.

 Illustrative images. Patterns may not match the product.








2 Optional Accessories

Possible Configurations

Refer to the chart and corresponding diagrams below for available configuration options.

	No Backer	Translucent Backer	Soft Sound® Backer
No light	A	B	C
Backlight		D	
InLine	E	F	G

Looking to combine backlight with acoustic performance in the same panel?
Check out our VaporSoft® line.



3

Available Finishes

Aluminum Panel

Powder Coat

Standard Finish




T-Grid White*
(Matte)



Arktura White
(Matte)



Brilliant White
(Gloss)



Silver Metallic
(Semi Gloss)



Jet Black
(Matte)

Powder Coat

Premium Finish



Aviator Gray
(Gloss)



Aviator Gray
(Matte)



Steel Gray



Shadow



Midnight



Coffee



Raw Umber



Caramel



Sandstone



Oat



Sunflower



Torch



Spirit Red
(Matte)



Azure



Blue Steel



Forest Green

Powder Coat

Premium Metallic Finish



Chilled Champagne
(Semi Gloss)



Burnished Bronze
(Semi Gloss)

Custom Powder Colors

We offer premium non-stock RAL and custom color match options as well. Contact your sales rep for more information.



Non-stock
RAL



Non-stock
Metallic


* This color was designed to pair with Armstrong color "WH" grid and trim.

③ Available Finishes

Optional Translucent Backer

Polycarbonate


Available in interior and UV stable exterior options.




Frosted

Optional Soft Sound® Backer


Soft Sound® Color Group A Standard



White



Snow



Marble



Heather Gray




Graphite



Carbon




Onyx




Apple



Tangerine




Lemon



Taupe



Sand




Kiwi



Whisper



Sky Blue








Denim


Soft Sound® Wood Texture Premium

① As with natural wood, variation in color and grain is expected and grain will not align across panels.

Core




Face




Gray Ash




White Oak



Golden Oak



Oak



American Walnut




Charred Oak


Core



Face



Charred Ash



Ebony

① Due to the nature of non-woven materials, light may pass through Soft Sound® in any thickness or color. A translucent appearance is most apparent in lighter colors and thin material when a light source is present behind the material. Arkтура makes no claims or warranties about the material performing as opaque in any circumstance. To verify a products performance for light transmittance, a mockup of the specific intended use is recommended.

4 Product Specifications & Certifications

System Specs

Panel Size (WxHxD)	600 X 1200 X 38
Material	Aluminum
Openness in Plan	24%
Fire Rating	ASTM E84 - Class A 13501-1 B-s1, d0
Acoustics (with optional Soft Sound® backer)	True NRC® 0.80: Ceiling ; E-300 Method True NRC® 0.75: Wall ; F-70 Method
Ceiling Attachment	Torsion Grid (By Others)
Wall Attachment	Vertika® Wall (Refer to Vertika® Brochure)
Accessibility	Torsion Spring Hinge
Trimmability	Yes, per installation manual
Optional Accessories	Acoustic Backer, Translucent Backer, Backlight, InLine Light, Torsion Spring Adapter Clip


Patented
Copyright © 2015-2022 Arktura LLC. All rights reserved.

Lighting Specs

Arktura Backlighting

Available in dimmable low and high output variations, gives you the power to illuminate spaces and create dynamic visual effects.

Ceiling




Vertika® Wall




Sections

Front view



Side view




Photometric

Located At Horizontal Angle = 0, Vertical Angle = 0

#1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)

#2 - Horizontal Cone Through Vertical Angle (0) (Through Max. Cd.)



Specs


Product Features	Arktura Backlighting Eco	Arktura Backlighting
Total Lumens	2250 Lm/2x4 Panel	4050Lm/2x4 Panel
Delivered Lumens	2250 Lm/2x4 Panel	4050Lm/2x4 Panel
Power Consumption	25 Watts 2x4 Panel	45 Watts 2x4 Panel
CRI	80+	
Color Temperatures	3000k, 3500k, 4000k (Other temperatures on request)	
Size (LxWxD)	600 X 1200 X 76	
UL Rating	Listed	
Voltage	24 Volts	
Dimming Options	MLV, 1-10V, 0-10V	
Plenum Rated Wire	Standard	

Lighting Specs


Arktura InLine Lighting

Makes it easy to seamlessly integrate linear lighting into the design of your paneling.


Ceiling



Vertika® Wall






Side - Length Options



Specs

Product Features	Arktura InLine Eco	Arktura InLine
Total Lumens	640 Lm/Ft	1280 Lm/Ft
Delivered Lumens	480 Lm/Ft	960 Lm/Ft
Power Consumption	6W/Ft	12W/Ft
CRI	95+	
Color Temperatures	3000k, 3500k, 4000k (Other temperatures on request)	
Size (LxWxD)	600 X 50 X 32 X 2438 X 50 X 32	
UL Rating	Recognized	
Voltage	24 Volts	
Dimming Options	MLV, 1-10V, 0-10V	
Plenum Rated Wire	Standard	

Elevations




Photometric

Located At Horizontal Angle = 0, Vertical Angle = 0

#1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)

#2 - Horizontal Cone Through Vertical Angle (0) (Through Max. Cd.)




Product Line

Design Options

Vapor® offers a growing library of metal panels in preconfigured seamlessly tileable patterns that can also be mixed and matched as desired. For additional acoustic performance, take a look at our Soft Sound® faced VaporSoft®.



VAPOR® TRAIL




VAPOR® PIXEL



VAPOR® CUMULA




VAPOR® BYTE




VAPOR® CLUSTER




VAPOR® SYNTAX



VAPOR® SHIFT



VAPOR® CORA



VAPOR® FREQUENCY




VAPOR® LIANA

Product Line

Design Options



VAPOR® SKY



VAPOR® GRADIENT




VAPOR® ELEMENT




VAPOR® BLOOM




VAPOR® BREEZE



VAPOR® SOLID



VAPOR® TRANSIT



VAPOR® VERVE



VAPOR® BOND